



A BILL FOR AN ORDINANCE

TO AMEND CHAPTER 21A, REVISED ORDINANCES OF HONOLULU 1990, (FLOOD HAZARD AREA ORDINANCE), RELATING TO FLOOD HAZARD AREAS.

BE IT ORDAINED by the People of the City and County of Honolulu:

SECTION 1. Purpose and intent. The purpose of this ordinance is to amend the Flood Hazard Area Ordinance, Chapter 21A, Revised Ordinances of Honolulu 1990, to adopt language and construction standards required by the Federal Emergency Management Agency, establish fees for the processing and administering of Flood Hazard Area related permits, and for housekeeping purposes.

SECTION 2. Section 21A-1.3 (“Administration”) Revised Ordinances of Honolulu 1990, is amended to read as follows:

“Sec. 21A-1.3 Administration

(i) Fees:

	<u>Type of Permit</u>	<u>Fee</u>
(1)	<u>Floodway Permit</u>	<u>\$600.00</u>
(2)	<u>Flood Variance</u>	<u>\$600.00</u>
(3)	<u>Letter of Map Amendment (LOMA), and Revision Based on Fill (LOMR-F)</u>	<u>\$300.00</u>
(4)	<u>Letter of Map Revision (LOMR), and Physical Map Revision (PMR)</u>	<u>\$600.00</u>
(5)	<u>Flood Hazard Area Interpretation</u>	<u>\$150.00”</u>

SECTION 3. Section 21A-1.7 (“Floodway area”) Revised Ordinances of Honolulu 1990, is amended to read as follows:



A BILL FOR AN ORDINANCE

"Sec. 21A-1.7 Floodway area.

- (a) A floodway permit shall be obtained from the director before approval or issuance of any other permits for all new construction or substantial improvements of structures within the floodway area."

SECTION 4. Section 21A-1.8 ("Flood fringe area") Revised Ordinances of Honolulu 1990, is amended to read as follows:

"Sec. 21A-1.8 Flood fringe area.

- (e) New construction and substantial improvements of below-grade crawlspaces shall be constructed in accordance with the requirements of FEMA Technical Bulletin 11-01 and amendments thereto. Designs for meeting this requirement shall be certified by a licensed engineer or architect.
- (f) Accessory residential structures of less than 600 square feet which are used solely for parking and/or limited storage, and are constructed with the lowest floor below the base flood elevation must be designed to meet the following minimum criteria:
- (1) The structure must be anchored to resist flotation, collapse, and lateral movement;
 - (2) Any portion of the structure located below the base flood elevation must be constructed of flood-resistant materials;
 - (3) The structure must be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters in accordance with the provisions of preceding subsection (c);
 - (4) All mechanical and utility equipment housed inside the structure must be elevated to or above the base flood elevation;
 - (5) The use of the structure must be limited to parking and/or limited storage.

Designs for meeting this requirement shall be certified by a licensed engineer or architect."



A BILL FOR AN ORDINANCE

SECTION 5. Section 21A-1.13 ("Substantial Improvements") Revised Ordinances of Honolulu 1990, is amended to read as follows:

"Sec.21A-1.13 Substantial improvements.

All structures proposed to be substantially improved must be brought into compliance with the standards and provisions of this chapter. For the purpose of determining substantial improvement, the market value of a structure and the cost of the proposed improvements to the structure shall be provided by the applicant from the following sources:

- (a) Itemized estimates made by an independent professional construction estimator;
- (b) Appraisals prepared by an independent licensed appraiser, including appraisals of market value;
- (c) Calculations based on square foot cost factors published in building cost estimating guides recognized by the building construction industry, and signed and stamped by an independent licensed engineer or architect.

The director may require additional or revised documentation should the estimated market value or cost of improvements appear to be inconsistent with the specific characteristics of the building."

SECTION 6. Section 21A-1.14 ("Certification Standards") Revised Ordinances of Honolulu of Honolulu 1990, is amended to read as follows:

"Sec. 21A-1.14 Certification standards.

[(a)] Pre-construction, during-construction, and post-construction certification of elevation and floodproofing of new construction, development and improvements within the special flood hazard areas shall be submitted to the director and shall be maintained as a matter of public record.

[(b)] (a) Pre-construction certification.

Requirements for approval of the building permit shall include the following items, as applicable, and any additional items as required by the director to promote public welfare and safety:



A BILL FOR AN ORDINANCE

(1) Certification of building plans.

Each set of building plans shall include a current topographic survey map prepared by a licensed surveyor, and shall be signed and stamped by a licensed engineer or architect certifying the accuracy of the flood boundary and elevation information.

(2) Flood Hazard Certification.

The City and County of Honolulu applicable flood hazard certification form, as amended, shall be completed and signed and stamped by a licensed engineer or architect.

(3) Floodproofing Certification.

The Federal Emergency Management Agency "Floodproofing Certificate" form, as amended, shall be completed and signed and stamped by a licensed engineer or architect.

(4) Certification of No-rise Determination.

For all construction and improvements in the floodway, the Federal Emergency Management Agency "No-rise Certification" form, as amended, shall be completed and signed and stamped by a licensed engineer.

[(c)] (b) During-construction certification.

Upon placement of the lowest floor, including the basement, and prior to further vertical construction of a new or substantially improved structure in the special flood hazard area, the Federal Emergency Management Agency "Elevation Certificate", as amended, shall be completed and signed and stamped by a licensed surveyor.

[(d)] (c) Post-construction certification.

As a condition for the closing of the building permit or issuance of a certificate of occupancy for a new or substantially improved structure in the special flood hazard area, the Federal Emergency Management Agency "Elevation Certificate", as amended, shall be completed and signed and stamped by a licensed surveyor, engineer or architect."



A BILL FOR AN ORDINANCE

SECTION 7. Ordinance material to be repealed is bracketed and new material is underscored. When revising, compiling, or printing this ordinance for inclusion in the Revised Ordinances of Honolulu, the revisor of ordinances need not include the brackets, the bracketed material, or the underscoring.

SECTION 8. This ordinance shall take effect upon its approval.

INTRODUCED BY:

[Handwritten signature]

(br)

DATE OF INTRODUCTION:

JUN 27 2016

Honolulu, Hawaii

Councilmembers

APPROVED AS TO FORM AND LEGALITY:

Deputy Corporation Counsel

APPROVED this _____ day of _____, 2016.

KIRK CALDWELL, Mayor
City and County of Honolulu